

LOW-VOLTAGE HEADS

ISO Head

DESCRIPTION

16 watt, 850+ lumen directional LED head. The precision lines of the heat sink peak through the sleek outer housing creating a look that speaks to the functional performance of the luminaire. The LED is easily field-replaceable and upgradeable due to the solderless connector. The heat sink remains with the fixture minimizing any waste at the end of the lamp module's life. The head rotates 360° and pivots 90° to direct the beam. Integrated lens holder accommodates one lens or louver (sold separately). Dimmable to 10% with low-voltage electronic or magnetic dimmer (based on the transformer).



ACCESSORIES & OPTICAL CONTROLS

Colored Lens, Dichroic Lens, Diffuser Lens, Eggcrate Louver, Linear Spread Lens, Soft Focus Lens, UV Filter

WEIGHT

1.58lb / 0.72kg ±

ORDERING INFORMATION

700 SYSTEM	ISO	CRI	COLOR TEMP	BEAM SPREAD	LENGTH (A)	FINISH	LAMP				
FJ	FREEJACK	8	80 CRI	27	2700K	20	20°	03	3"	S SATIN NICKEL	-LED LED
MP	MONOPOINT	9	90 CRI	30	3000K	30	30°	06	6"	W WHITE	
MO	MONORAIL			827	2700K	50	50°	12	12"		
MO2	TWO-CIRCUIT MONORAIL			830	3000K			18	18"		
				930	3000K						

Note: MP includes 4" Round Flush Canopy.

When installing LED option on MO2 only magnetic transformers may be used.



TECH LIGHTING®
 7400 Linder Avenue T 847.410.4400
 Skokie, Illinois 60077 F 847.410.4500

Tech Lighting, L.L.C.

700 ____ ISO _____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____

