

LOW-VOLTAGE HEADS

Sprocket Head

DESCRIPTION

Sleek Sprocket, with its removable handle, has many accessory options. Head rotates 360° and pivots 300° on vertical axis. Low-voltage, MR16 lamp of up to 75 watts (not included).

INSTALLATION


Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system.

ACCESSORIES & OPTICAL CONTROLS

Backlight Shield, Barndoors, Flight Paper, Louver Lens Holder, Snap Louver Lens Holder, Spy Accessory

WEIGHT

0.35-0.9lb / 0.16-0.41kg ±



ORDERING INFORMATION

700 SYSTEM SP	LENGTH (A)	FINISH
FJ FREEJACK	1 1"	Z ANTIQUE BRONZE
MP MONOPOINT	3 3"	C CHROME
MO MONORAIL	6 6"	S SATIN NICKEL
MO2 TWO-CIRCUIT MONORAIL	12 12"	
WMO WALL MONORAIL	18 18"	
	24 24"	

Note: MP includes 4" Round Flush Canopy.



700 ____ SP ____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____



©2013 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.